


| REV. | REVISIONS      | REC. | DATE      | REV. | REVISIONS | REC. | DATE |
|------|----------------|------|-----------|------|-----------|------|------|
| 2    | △SHAPE MODIFY. |      | '03.10.20 |      |           |      |      |
| 3    | 整理圖框           |      | '05.01.20 |      |           |      |      |

|  |   |                   |               |                  |                                |        |
|--|---|-------------------|---------------|------------------|--------------------------------|--------|
| DRAWN & DRAFTED BY<br>LIN TIAN SHENG   | TOLERANCES  |                   | ANGLE:        | TITLE:           |                                |        |
|  | 0<L≤4 ±0.1  | pin pitch<br>±0.2 | ±1°           | T-H BOBBIN EF-25 |                                |        |
| CHECKED & APPROVED BY  | 4<L≤16 ±0.2   |                   | UNIT:         | BOBBIN MATERIAL: | UL REC.                        |        |
|  | 16<L≤63 ±0.3  |                   | MM            | PHENOLIC T375J   | UL 94V-0                       |        |
|  PIN SHINE INDUSTRIAL CO.,LTD.<br>TEL:886-2-22990545      FAX:886-2-22990546 | ORIGIN:   | ZZ                | PIN MATERIAL: | CP WIRE          | PIN TENSION LOAD:<br>1.5kg MIN |        |
|  |  |                   | DATE:         | DEC.14'1998      | DRAWING NO.                    | P-2528 |