



電鍍規格：
 NI:0.5~3.0um
 Sn:4~10um
 霧面全錫

注：1:熱處理硬度管控範圍：350HV~400HV
 2:(B)尺寸沖壓時須管控在9.7±0.1範圍內

REV.	REVISIONS REC.	DATE.	REV.	REVISIONS REC.	DATE
11	電鍍規格設變	08/20/'10	6	Correct DIM (B) as 9.8+/-0.1(was 9.7+/-0.2)	'04.07.25
5	UPDATE THE DRAWING, CORRECT SOME DIM. ACCORDING TO THE CURRENT TOOL.	'04.01.12	7	Correct DIM (B) as 9.8+0.1/-0.2 (was 9.8+/-0.1)	'07.07.18
			8	CLIP MATERIAL:SK7 1/2H->SK7 HV	'08.04.12

DRAWN & DRAFTED BY LI WEI	TOLERANCES		ANGLE: ±1°	TITLE: CLIP RM-6	
	0<L≤4 ±0.1	pin pitch ±0.2	UNIT: MM	CLIP MATERIAL: SK7 HV	UL REC.
CHECKED & APPROVED BY	4<L≤16 ±0.2		ORIGIN: SZ	PIN MATERIAL:	PIN TENSION LOAD:
	16<L≤63 ±0.3			DATE: 08/20/'2010	DRAWING NO. C-006
PIN SHINE INDUSTRIAL CO.,LTD. TEL:886-2-22990545 FAX:886-2-22990546					REV. 11