



△電鍍規格：Sn 100% 4~10um Ni 1.0~2.0um

此鐵夾是在C-144基礎上新增缺口的機種

注：腳掌面需有2/3平面平貼平板。

| REV. | REVISIONS | REC. | DATE.    | REV. | REVISIONS | REC. | DATE. |
|------|-----------|------|----------|------|-----------|------|-------|
| 2    | 新增電鍍規格    |      | 13.03.15 |      |           |      |       |
|      |           |      |          |      |           |      |       |

|  |          |                  |                   |         |             |                |                   |
|--|----------|------------------|-------------------|---------|-------------|----------------|-------------------|
| DRAWN & DRAFTED BY   | QIN MENG | TOLERANCES       |                   | ANGLE:  | TITLE:      |                |                   |
|  |          | 0 < L ≤ 4 ± 0.1  | pin pitch ± 0.2   | ± 1°    | CLIP EE-5.0 |                |                   |
| CHECKED & APPROVED BY  |          | 4 < L ≤ 16 ± 0.2 |                   | UNIT:   | MM          | CLIP MATERIAL: | PHOSPHOR BRONZE   |
|  |          |                  | 16 < L ≤ 63 ± 0.3 | ORIGIN: | DG          | PIN MATERIAL:  | PIN TENSION LOAD: |
| <b>PIN SHINE INDUSTRIAL CO., LTD.</b><br>TEL: 886-2-22990545 FAX: 886-2-22990546 |          |                  |                   |         | DATE:       | DRAWING NO.    | REV.              |
|  |          |                  |                   |         | APR.05.2007 | C-144-1        | 2                 |