



| REV. | REVISIONS REC. | DATE | REV. | REVISIONS REC. | DATE |
|------|--------------------------|-----------|------|----------------|------|
| 1 | (I)0.8->0.92 | '99.04.20 | | | |
| 2 | (L)5.4->5.5 (F) 6.9->7.0 | '01.08.07 | | | |
| 3 | 端子硬度變更為 H Δ | '17.08.17 | | | |

| | | | | | |
|--|--------------|-------------------|------------------|----------------------|----------|
| DRAWN & DRAFTED BY CHEN HAI QING | TOLERANCES | | ANGLE: | TITLE: | |
| | 0<L≤4 ±0.1 | pin pitch ±0.2 | ±1° | SMD BASE 7.0X7.0X0.5 | |
| CHECKED & APPROVED BY | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | UL REC. |
| | 16<L≤63 ±0.3 | | MM | LCP E4008 | UL 94V-0 |
| ORIGIN: DG | | | PIN MATERIAL: | PIN TENSION LOAD: | |
| PIN SHINE INDUSTRIAL CO., LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | | C5191 H Δ | 1.5KG MIN | |
| | | | DATE: | DRAWING NO. | REV. |
| | | | OCT.16 '2004 | SB-004 | 3 |