



SEC. A-A

注:
 PIN 電鍍
 ② NI:1.2~2.5um
 SN:5~7um
 標*為重點管控尺寸

REV.	REVISIONS REC.	DATE	REV.	REVISIONS REC.	DATE
1	M:φ4.35→φ4.35±0.1 H:3.0→3.0±0.2 G:4.2→4.7±0.2		2	產品尺寸公差設變,詳情見 ②	10/11/12
	D:7.0±0.15→7.0±0.1 B:8.1±0.15→8.1±0.1		3	產品尺寸設變,詳情見 ③	11/14/12
	ADD DIMENSION:φ6.5±0.1 2.0±0.1 4.4±0.1 0.5	04/09/05'			

DRAWN & DRAFTED BY CHEN FEI	TOLERANCES		ANGLE:	TITLE:	
	0<L≤4 ±0.1	COPLANARITY 0.1MAX	±1°	SMD BASE SUMIDA-CMS65	
CHECKED & APPROVED BY	4<L≤16 ±0.2		UNIT:	BOBBIN MATERIAL:	UL REC.
	16<L≤63 ±0.3		MM	PHENOLIC PM9630	UL 94V-0
PIN SHINE INDUSTRIAL CO., LTD. TEL:886-2-22990545 FAX:886-2-22990546			ORIGIN:	PIN MATERIAL:	PIN TENSION LOAD:
			SZ	PHOSPHOR BRONZE	1.5kg MIN
			DATE:	DRAWING NO.	REV.
			NOV.14 '2012	SB-008-1	3