



注：
PIN 電鍍
NI:1.2~2.5um
SN:5~10um

REV.	REVISIONS REC.	DATE	REV.	REVISIONS REC.	DATE
1	M: $\phi 4.35 \rightarrow \phi 4.35 \pm 0.1$ H: $3.0 \rightarrow 3.0 \pm 0.2$ G: $4.2 \rightarrow 4.7 \pm 0.2$		2	產品尺寸公差設變，詳情見 2	10/11/12
	D: $7.0 \pm 0.15 \rightarrow 7.0 \pm 0.1$ B: $8.1 \pm 0.15 \rightarrow 8.1 \pm 0.1$		3	產品尺寸設變，詳情見 3	11/14/12
	ADD DIMENSION: $\phi 6.5 \pm 0.1$ 2.0 ± 0.1 4.4 ± 0.1	04/09/05'	4	按照苏品图纸重新整理图面. 4	13/01/22

DRAWN & DRAFTED BY 管鑫海	TOLERANCES		ANGLE:	TITLE:		
	0<L≤4 ±0.1	pin pitch ±0.2	±1°	SMD BASE SUMIDA-CMS65		
CHECKED & APPROVED BY	4<L≤16 ±0.2		UNIT:	BOBBIN MATERIAL:	UL REC.	
	16<L≤63 ±0.3		MM	PHENOLIC PM9630	UL 94V-0	
ORIGIN: DG			PIN MATERIAL:	PIN TENSION LOAD:		
PIN SHINE INDUSTRIAL CO.,LTD.			PHOSPHOR BRONZE	1.5KG MIN		
TEL:886-2-22990545	FAX:886-2-22990546		DATE:	DRAWING NO.	REV.	
			NOV.14'2012	SB-008-1	4	